









**UNITY**
**DESIGN DUALITY**

**INTERGRATE**  
800FB | 800CB

**PROXIMITY**  
700FB | 700CB

**TOGETHER**  
600FB | 600CB

**COLLECTIVE**  
500FB | 500CB

**MERGE**  
400FB | 400CB

**HARMONY**  
300FB | 300CB

**SYNERGY**  
200FB | 200CB

**ACCORD**  
100FB | 100CB

FB – Flexi Bak®  
CB – Comfi Bak®

**SPECIFICATIONS**

<b>Collection</b>	Design Duality
<b>Product</b>	Unity
<b>Product Category</b>	Carpet Tile
<b>Construction</b>	Multi-level Loop
<b>Yarn/Fibre</b>	Solution Dyed Nylon
<b>Pile Weight</b>	610g/m <sup>2</sup> (18oz)
<b>Pile Height</b>	4mm
<b>Gauge</b>	1/12
<b>Tile Size</b>	500 x 500mm
<b>Total Thickness</b>	6.5mm Flexi Bak®   9.0mm Comfi Bak®
<b>Total Weight</b>	3.5kg/m <sup>2</sup> Flexi Bak®   4.2kg/m <sup>2</sup> Comfi Bak®
<b>Carton Size</b>	5m <sup>2</sup>

**CUSTOM OPTIONS**

<b>Flexi Bak®</b>	In stock
<b>Comfi Bak®</b>	In stock
<b>Thermo Bak®</b>	50m <sup>2</sup> minimum
<b>Shapes by Signature®</b>	50m <sup>2</sup> minimum

**INSTALLATION METHODS**


ASHLAR



QUARTER TURN



BRICK



DIRECTIONAL



RANDOM

**PERFORMANCE**

<b>Dimensional Stability</b>	<0.15%
<b>Backing</b>	Flexi Bak®   Comfi Bak®
<b>Electrostatic Propensity</b>	<3.0kv
<b>Recommended Adhesive</b>	RLA Polymers GS300
<b>ACCS Rating</b>	Commercial Extra Heavy Duty
<b>Warranty</b>	15 Year
<b>Fire Rating ISO 9239.1</b>	>4.5kw/m <sup>2</sup> Critical Radiant Flux Suitable all areas
<b>Stain/Soil</b>	Ultra Gard

**SUSTAINABILITY**

GreenTag® GreenRate Level A  
EPDs And Declare Labels  
WELL & LBC Eligible

**TECHNICAL DOCUMENTS**

[Technical Information Guide](#)  
[Care and Maintenance Guide](#)  
[Warranty Guide](#)

Our manufacturing process ensures no two tiles are the same. Please note that there may be batch variations from different dye lots.