

intellitiles
earth II 




carpet tiles
featuring GreenTag certification




innovation & inspiration

| *Signature*[®]
floorconcepts


for 100% GreenStar Points




alps 2601




hemisphere 2652



oceans 2603



longitude 2703°



atmosphere 2501

product construction
yarn/fibre
pile weight
pile height
gauge
tile size
total thickness

carton size
total weight

dimensional stability
backing

earth II
 multi-level loop
 solution dyed nylon
 612g/m²
 3.5mm
 1/12
 500mm x 500mm
 6.0mm (Thermo Bak™)
 9.0mm (Comfi Bak®)
 5m²
 4.6kg/m² (Thermo Bak™)
 4.3kg/m² (Comfi Bak®)
 <0.15%
 Thermo Bak™, Comfi Bak®

electrostatic propensity
fire rating ISO 9239.1

recommended adhesive
installation method
availability
Comfi Bak® option
Shapes™ option
traffic
warranty
stain/soil
sustainability

<3.0kv
 5.4kw/m² critical radiant flux (Thermo Bak™)
 5.0kw/m² critical radiant flux (Comfi Bak®)
 RLA Polymers GS300
 quarter turn
 in stock
 50m² minimum
 50m² minimum
 extra heavy duty commercial
 15 year limited
 Ultra Gard
 GreenTag® GreenRate Level A certified
 EPD and Declare labels
 WELL eligible

Traffic

Extra Heavy Duty Commercial

Warranty

15 Year Limited



Declare.

Signature[®]
 floorconcepts

au 03 9401 0888
 nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz

°also stocked with Comfi Bak®