

PURE PLANKS

**BASE**




BASE FOG 7000PL

au 1800 150 554  
nz 0800 150 555  
[signaturefloors.com.au](http://signaturefloors.com.au)  
[signaturefloors.co.nz](http://signaturefloors.co.nz)

*Signature*

**BASE** PURE PLANKS




**SPECIFICATIONS**

<b>Collection</b>	Pure Planks
<b>Product</b>	Base
<b>Product Category</b>	Carpet Plank
<b>Construction</b>	Multi-level Loop with Tipshear
<b>Yarn/Fibre</b>	Solution Dyed Nylon
<b>Pile Weight</b>	986g/m <sup>2</sup> (29oz)
<b>Pile Height</b>	5.5mm
<b>Gauge</b>	1/10
<b>Tile Size</b>	250mm x 1000mm
<b>Total Thickness</b>	8.5mm
<b>Total Weight</b>	6.0kg/m <sup>2</sup>
<b>Carton Size</b>	4m <sup>2</sup>

**CUSTOM OPTIONS**

<b>Thermo Bak<sup>®</sup></b>	In stock
<b>Flexi Bak<sup>®</sup></b>	100m <sup>2</sup> minimum
<b>Comfi Bak<sup>®</sup></b>	100m <sup>2</sup> minimum
<b>Shapes by Signature<sup>®</sup></b>	100m <sup>2</sup> minimum

**INSTALLATION METHODS**



**PERFORMANCE**

<b>Dimensional Stability</b>	<0.15%
<b>Backing</b>	Thermo Bak <sup>®</sup>
<b>Electrostatic Propensity</b>	<3.0kv
<b>Recommended Adhesive</b>	RLA Polymers GS300
<b>Rating</b>	Commercial Extra Heavy Duty
<b>Warranty</b>	15 Year Limited
<b>Fire Rating ISO 9239.1</b>	5.3kw/m <sup>2</sup> Critical Radiant Flux Suitable all areas
<b>Stain/Soil</b>	Ultra Gard

**SUSTAINABILITY**

GreenTag<sup>®</sup> GreenRate Level A  
 EPDs And Declare Labels  
 WELL & LBC Eligible

**TECHNICAL DOCUMENTS**

[Technical Information Guide](#)  
[Care and Maintenance Guide](#)  
[Warranty Guide](#)

Our manufacturing process ensures no two planks are the same. Please note that there may be batch variations from different dye lots.

