

SIGNATURE FLOORS LAMINATE FLOORING BPIR DECLARATION

Version 1.0 June 2024



DESIGNATED BUILDING PRODUCT: Class 1

DECLARATION

Signature Floorcoverings Pty Ltd (branded as Signature Floors) has provided this declaration to satisfy the provisions of the **Building (Building Product Information Requirements) Regulations 2022**.

COMPANY DETAILS

Name	Signature Floorcoverings Pty Ltd (T/A Signature Floors)
Role	Supplier
NZBN	9429041854273
Address	15 Bath St, Parnell, Auckland 1052
Website	www.signaturefloors.co.nz
Email	info@signaturefloors.co.nz
Phone	09 414 2001

DESCRIPTION OF BUILDING PRODUCT

Signature Floors supply a range of laminate flooring planks that are designed to provide a wood-look finish.

The laminate flooring is made from melamine resin and fibreboard and is manufactured by **Atroguard®**.

The flooring must be loose-laid over an underlay in accordance with the Signature Floors Installation guidelines. Signature Floors recommends several underlays as well as supplying their own brand.

Signature Floors Laminate Flooring Collections

PARADISE

The Paradise range of laminate flooring planks are 236 x 2260 mm in size and 12 mm thick with a pressed bevel edge.

The range is supplied in a variety of natural wood-grain finishes.

It has an abrasion resistance of AC4 (commercial) and, when tested to ISO 9239.1, achieves a critical radiant flux of 9.3kW/m² which exceeds the minimum requirement of 4.5kW/m². It may therefore be used in all areas where C3.4 (b) obligations apply.

When tested, Paradise laminate flooring planks achieve slip resistance of P2 which is equivalent to an SRV between 25 and 34 which means that it is not suitable for use in access routes.

Paradise flooring is suitable for use with water-based underfloor heating systems.

See [here](#) for more information.

WHITSUNDAYS - AQUAPLANK

The Whitsundays Aquaplank range of laminate flooring planks are 238 x 1800 mm in size and 12 mm thick with a V groove on all four edges.

The range is supplied in a variety of embossed natural wood-grain finishes.

It has an abrasion resistance of AC4 (commercial) and, when tested to ISO 9239.1, achieves a critical radiant flux of 6.3kW/m² which exceeds the minimum requirement of 4.5kW/m². It may therefore be used in all areas where C3.4 (b) obligations apply.

When tested, Whitsundays Aquaplank laminate flooring planks achieve slip resistance of TBC P2 which is equivalent to an SRV between 25 and 34 which means that it is not suitable for use in access routes.

Whitsundays Aquaplank flooring is suitable for use with underfloor heating.

See [here](#) for more information.

NEXUS - PLANTINO

The Plantino Nexus range of laminate flooring planks are 193 x 1830 mm in size and 12 mm thick with a V groove on all four edges.

The range is supplied in a variety of natural wood-grain finishes.

It has an abrasion resistance of AC4 (commercial) and, when tested to ISO 9239.1, achieves a critical radiant flux of 9.3kW/m² which exceeds the minimum requirement of 4.5kW/m². It may therefore be used in all areas where C3.4 (b) obligations apply.

When tested, Platino Nexus laminate flooring planks achieve slip resistance of P3 which is equivalent to an SRV between 35 and 44. This means that Plantino Nexus planks may only be used in access routes that are not expected to become wet in normal use.

Plantino Nexus flooring is suitable for use with water-based underfloor heating systems.

See [here](#) for more information.

Slip resistance applies to **access routes** which are defined as a continuous route that permits people and goods to move between the apron or construction edge of the building to spaces within a building, and between spaces within a building.

Watertightness of the plank junctions is ensured through the edge detail combined with the redundancy provided by the waterproof underlay with self-adhered joints. This, along with the performance of laminates (which has been established through in-service), means that the use of Signature Floors laminate flooring is suitable for use in areas subject to water splash.

Signature Floors, originally an Australasian company, was founded in 1989. It has begun working towards sustainability. The Australian arm is certified **Carbon Neutral**, and most products are Green Tag Certified and/or have a Declare label. In 2023 it was purchased by the **Beaulieu International Group** (BIG). BIG has an active focus on **sustainability** and have developed a strategy to achieve a zero footprint by 2030. As part of the BIG group, Signature Floors is now part of this approach.

CONTRIBUTION TO BUILDING WORK CODE OBLIGATIONS

Signature Floors rely on third party testing and the claims of the manufacturer in making the following performance claims.

When installed in accordance with Signature Floors installation requirements, the laminate flooring planks *may* contribute to compliance with the applicable performance criteria in respect of:

- B1 (Structure): B1.3.1, B1.3.2, B1.3.3 (a, b, e, j, q)
- B2 (Durability): B3.2.1 (c)
- C3 (Fire Affecting Areas Beyond The Fire Source): C3.4 (b)
- D1 (Access Routes): D1.3.3 (d)
- E3 (Internal Moisture): E3.3.3, E3.3.5, E3.3.6
- F2 (Hazardous Building Materials): F2.3.1.

FOR FURTHER INFORMATION

Signature Floors laminate plank range of products must be used in accordance with all Signature Floors requirements.

For supporting information, refer to [Signature Floors](#).

RESPONSIBLE PERSON

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm Signature Floors laminate flooring planks, as referred to in this statement, are not subject to a warning or ban under **s26 of the Building Act**.

Signed for and on behalf of Signature Floorcoverings Pty Ltd (branded as Signature Floors):

Richard Slade

Richard Slade
GENERAL MANAGER (NZ)

June 2024

SIGNATURE FLOORCOVERINGS PTY LTD

15 BATH ST, PARNELL, AUCKLAND 1052

09 414 2001 | www.signaturefloors.co.nz

Uncontrolled in printed format

Signature
signaturefloors

SIGNATURE FLOORCOVERINGS PTY LTD

15 BATH ST, PARNELL, AUCKLAND 1052

09 414 2001 | www.signaturefloors.co.nz

Uncontrolled in printed format

Signature
signaturefloors